

Aluminized Fiberglass Satin

Style Number	1025
Description	FGD375Satin
Coating Face	Gentex® Dual Mirror® Aluminized Fabric
Certifications	EN 531 (Pass A, B1, C4, D1, and E1)
	EN ISO 11612:2008 (Pass A1, A2, B1, C4, D1, and E1) (Pass 6.2, 6.5.1 and 6.5.2)

Characteristics

	Test Method	English	Metric
Areal Weight	ASTM D3776	11.0 oz / sq yd	375 gms / sq m
Thickness	ASTM D1777	0.012 in	0.30 mm
Breaking Strength	ASTM D5034		
Warp		350.0 lbs	1557.0 N
Fill		250.0 lbs	1112.0 N
Tear Strength	ASTM D1424		
Elmendorf Tear			
Warp		CNM lbs	CNM N
Fill		10.0 lbs	44.0 N
Flame Resistance	ASTM D6413		
After Flame		1.0 sec	1.0 sec
Char Length		0.50 in	1.3 cm
Radiant Reflectivity	MIL-C-24929A	10.0 sec	10.0 sec

Style Number: 1025

Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, www.gentexcorp.com/aluminizedfabric.

GENTEX®

DUAL
MIRROR®