

Aluminized Meta Aramid Twill	
Style Number	1056
Description	MA290Twill
Coating Face	Gentex® Dual Mirror® Aluminized Fabric
Certifications	NFPA® 1971-2018

Characteristics

	Test Method	English	Metric
Areal Weight	ASTM D3776	8.5 oz / sq yd	290 gms / sq m
Thickness	ASTM D1777	0.014 in	0.36 mm
Breaking Strength	ASTM D5034		
Warp		250.0 lbs	1112.0 N
Fill		150.0 lbs	667.0 N
Tear Strength	ASTM D1424		
Elmendorf Tear			
Warp		6.0 lbs	27.0 N
Fill		4.0 lbs	18.0 N
Flame Resistance	ASTM D6413		
After Flame		2.0 sec	2.0 sec
Char Length		4.0 in	10.0 cm
Radiant Reflectivity	NFPA 1971-2013	20.0 sec	20.0 sec

Style Number: 1056

Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, www.gentexcorp.com/aluminizedfabric.

GENTEX®

**DUAL
MIRROR**®