

## Aluminized PREOX / PFR Rayon Knit Fleece

<b>Style Number</b>	1079B
<b>Description</b>	PX PFR 405 Fleece
<b>Coating Face</b>	Gentex® Dual Mirror® Aluminized Fabric
<b>Certifications</b>	ISO EN 11612 HR (PASS A1, A2, B1, C4, D3, E3, F1)

### Characteristics

	Test Method	English	Metric
<b>Areal Weight</b>	ASTM D3776	12 oz. / sq. yd.	405 grms./ sq. m
<b>Thickness</b>	ASTM D1777	0.030 inches	0.76 mm
<b>Tear Strength</b>	ASTM D1424		
Elmendorf Tear			
Wales		6.00 Lbs.	26N
Fill		4.00 Lbs.	17N
<b>Flame Resistance</b>	ASTM D6413		
After Flame		1.5 seconds	1.5 seconds
Char Length		1.0 inches	2.54 cm.
<b>Radiant Reflectivity</b>	MIL-C-24929A	20 seconds	20 seconds

**Style Number: 1079B**

### Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, [www.gentexcorp.com/aluminizedfabric](http://www.gentexcorp.com/aluminizedfabric).

**GENTEX**®

**DUAL  
MIRROR**®

**GENTEX<sup>®</sup>**

***DUAL  
MIRROR<sup>®</sup>***