

Aluminized Korspun I®	
Style Number	1081-1
Description	KOR645Plain-1
Coating Face	Gentex® Dual Mirror® Aluminized Fabric

Characteristics

	Test Method	English	Metric
Areal Weight	ASTM D3776	19.0 oz / sq yd	645 gms / sq m
Thickness	ASTM D1777	0.045 in	1.14 mm
Breaking Strength	ASTM D5034		
Warp		350.0 lbs	1557.0 N
Fill		100.0 lbs	445.0 N
Tear Strength	ASTM D1424		
Elmendorf Tear			
Warp		CNM	CNM
Fill		20.0 lbs	89.0 N
Flame Resistance	ASTM D6413		
After Flame		2.0 sec	2.0 sec
Char Length		0.5 in	1.3 cm
Radiant Reflectivity	MIL-C-24929A	30.0 sec	30.0 sec

Style Number: 1081-1

Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, www.gentexcorp.com/aluminizedfabric.

GENTEX®

**DUAL
MIRROR®**