

## Aluminized Korspun I®

<b>Style Number</b>	1081
<b>Description</b>	KOR645Plain
<b>Coating Face</b>	Gentex® Dual Mirror® Aluminized Fabric
<b>Certification</b>	EN 531 (Pass A, B2, C4, D3, E3)

### Characteristics

	Test Method	English	Metric
<b>Areal Weight</b>	ASTM D3776	19.0 oz / sq yd	645 gms / sq m
<b>Thickness</b>	ASTM D1777	0.045 in	1.14 mm
<b>Breaking Strength</b>	ASTM D5034		
Warp		400.0 lbs	1779.0 N
Fill		150.0 lbs	667.0 N
<b>Tear Strength</b>	ASTM D1424		
Elmendorf Tear			
Warp		CNM	CNM
Fill		45.0 lbs	200.0 N
<b>Flame Resistance</b>	ASTM D6413		
After Flame		2.0 sec	2.0 sec
Char Length		0.5 in	1.3 cm
<b>Radiant Reflectivity</b>	MIL-C-24929A	30.0 sec	30.0 sec

## Style Number: 1081

### Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, [www.gentexcorp.com/aluminizedfabric](http://www.gentexcorp.com/aluminizedfabric).

**GENTEX®**

**DUAL  
MIRROR®**