Aluminized / Para Aramid Ripstop Knit			
Style Number	1088		
Description	PA290Ripstop		
Coating Face	Gentex® Dual Mirror® Aluminized Fabric		
Certifications	NFPA® 1971-2018		
	EN 531 (Pass A, B1, C4, and E1)		
	EN ISO 11612:2010 HR (Pass A1, A2, B1, C4, D2, E3, and F1)		
	Tensile: Pass Tear: Pass		

Characteristics

	Test Method	English	Metric
Areal Weight	ASTM D3776	8.5 oz / sq yd	290 gms / sq m
Thickness	ASTM D1777	0.023 in	0.58 mm
Tear Strength			
Trapezoidal Tear	ASTM D5733		
Warp		35.0 lb	156.0 N
Fill		40.0 lb	178.0 N
Elmendorf Tear	ASTM D1424		
Warp		14.0 lbs	62.0 N
Fill		9.0 lbs	40.0 N
Flame Resistance	ASTM D6413		
After Flame		2.0 sec	2.0 sec
Char Length		1.0 in	2.54 cm
Radiant Reflectivity	NFPA 1971-2013	30.0 sec	30.0 sec

Style Number: 1088

Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about out full line of fabrics visit, www.gentexcorp.com/aluminizedfabric.

