

<b>Aluminized Para Aramid Twill</b>	
<b>Style Number</b>	1095
<b>Description</b>	PA255Twill
<b>Coating Face</b>	Gentex® Dual Mirror® Aluminized Fabric

### Characteristics

	<b>Test Method</b>	<b>English</b>	<b>Metric</b>
<b>Areal Weight</b>	ASTM D3776	7.5 oz / sq yd	255 gms / sq m
<b>Thickness</b>	ASTM D1777	0.014 in	0.36 mm
<b>Breaking Strength</b>	ASTM D5034		
Warp		300.0 lbs	1335.0 N
Fill		100.0 lbs	445.0 N
<b>Tear Strength</b>	ASTM D1424		
Elmendorf Tear			
Warp		20.0 lbs	89.0 N
Fill		10.0 lbs	445.0 N
<b>Flame Resistance</b>	ASTM D6413		
After Flame		1.0 sec	1.0 sec
Char Length		2.0 in	5.1 cm
<b>Radiant Reflectivity</b>	MIL-C-24929A	15.0 sec	15.0 sec

## Style Number: 1095

### Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, [www.gentexcorp.com/aluminizedfabric](http://www.gentexcorp.com/aluminizedfabric).

**GENTEX**®

**DUAL**  
**MIRROR**®