

Aluminized PBI® / Para Aramid Ripstop Knit

Style Number	1098
Description	PBPFR240Ripstop
Coating Face	Gentex® Dual Mirror® Aluminized Fabric
Certifications	NFPA® 1971-2018

Characteristics

	Test Method	English	Metric
Areal Weight	ASTM D3776	7.0 oz / sq yd	240 gms / sq m
Thickness	ASTM D1777	0.02 in	0.51 mm
Tear Strength			
Trapezoidal Tear	ASTM D5733		
Warp		22.0 lb	98.0 N
Fill		22.0 lb	98.0 N
Elmendorf Tear	ASTM D1424		
Warp		6.5 lbs	29.0 N
Fill		5.5 lbs	24.0 N
Flame Resistance	ASTM D6413		
After Flame		1.5 sec	1.5 sec
Char Length		1.0 in	2.54 cm
Radiant Reflectivity	NFPA 1971-2013	20.0 sec	20.0 sec

Style Number: 1098

Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, www.gentexcorp.com/aluminizedfabric.

GENTEX®

FlexIR®