

## Aluminized Preox® Herringbone

<b>Style Number</b>	1100-4
<b>Description</b>	PX575Herringbone
<b>Coating Face</b>	Gentex® Dual Mirror® Aluminized Fabric
<b>Certifications</b>	EN ISO 11612: 2010 HR (Pass A1, A2, B1, C4, D3, E3, F1)

### Characteristics

	Test Method	English	Metric
<b>Areal Weight</b>	ASTM D3776	17.0 oz / sq yd	575 gms / sq m
<b>Thickness</b>	ASTM D1777	0.03 in	0.76 mm
<b>Breaking Strength</b>	ASTM D5034		
Warp		240.0 lb	1076.0 N
Fill		160.0 lb	712.0 N
<b>Tear Strength</b>	ASTM D1424		
Elmendorf Tear			
Warp		10.0 lbs	44.0 N
Fill		15.0 lbs	67.0 N
<b>Flame Resistance</b>	ASTM D6413		
After Flame		1.0 sec	1.0 sec
Char Length		1.0 in	2.54 cm
<b>Radiant Reflectivity</b>	MIL-C-24929A	20.0 sec	20.0 sec

## Style Number: 1100-4

### Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, [www.gentexcorp.com/aluminizedfabric](http://www.gentexcorp.com/aluminizedfabric).

**GENTEX®**

**DUAL  
MIRROR®**