

Aluminized Woven Fiberglass

Style Number	1299-074
Description	Fiberglass Satin
Coating Face	Gentex® Dual Mirror® Aluminized Fabric
Certifications	EN 531 (Pass A, B1 and C4)

Characteristics

	Test Method	English	Metric
Areal Weight	ASTM D3776	5.3 oz / sq yd	180 gms / sq m
Thickness	ASTM D1777	0.006 in	0.15 mm
Breaking Strength	ASTM D5034		
Warp		100.0 lbs	445.0 N
Fill		50.0 lbs	220.0 N
Tear Strength	ASTM D1424		
Elmendorf Tear			
Warp		2.0 lbs	9.0 N
Fill		2.0 lbs	9.0 N
Flame Resistance	ASTM D6413		
After Flame		2.0 sec	2.0 sec
Char Length		1.0 in	2.54 cm
Radiant Reflectivity	MIL-C-24929A	10.0 sec	10.0 sec

Style Number: 1299-074

Comprehensive Fabric Line

Field proven for over 50 years, Gentex delivers the most durable aluminized fabrics in the industry. Each roll of Gentex Dual Mirror Aluminized Fabric is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs. To view and learn more about our full line of fabrics visit, www.gentexcorp.com/aluminizedfabric.

GENTEX®

**DUAL
MIRROR®**