

PureFlo 3000

Battery Charger PF3000-03-048

- Single battery charger for Lithium Ion Battery
- Used to charge PF3000-03-003 Battery
- Operational indictors



TECHNICAL SPECIFICATIONS

Battery Type	Lithium Ion PF3000-03-003
Input	100 – 2410V ~50/60 Hz 16W
Output	3.7V, 2.1A: 7.77VA
Housing	UL94V - 0
Housing Protection	IP 41
Dimensions	120 x 103.45 x 52.8mm
Approvals	CE / CEC / DOE
Standard	IEC/ EN60335-1. IEC/EN60335-2-29, UL1310

DISPLAY MODES

	LED 1 (RED)	LED 2 (GREEN)	LED 3 (GREEN)	LED 4 (GREEN)
No Battery				•
Low/High Temp	•			
Pre Charging	•			
CC Charging	•			
CC Charging After 25 Mins		•		
CV Charging		•	•	
Battery Full		•	•	•
Battery Failed				
Timer	•			•
Broken Plus Connections	•			•
Broken Thermistor Connections	•			•
Broken Minus Connections	•			•

Contact Us

Gentex is committed to designing innovative safety solutions that protect people from immediate and long-term health and safety hazards present in their work environments, while enhancing workplace performance. Contact us today for more information on PureFlo and our full line of industrial safety solutions. **Tel:** +44 (0) 1776 70442 **Email:** sales@gentexcorp.eu.com **Follow Us on LinkedIn:** pureflo-respiratory-protection