



AMP™ COMMUNICATION HEADSET
**CONNECTORIZED
DOWNLEAD CABLE**

SMAHT ICS U174



Connects AMP Headsets to Push-to-Talks Using U94 Inputs

COLOR



BLACK - 21"
1003276-01-0021



BLACK - 30"
1003276-01-0030



BLACK - 60"
1003276-01-0060

This product is covered by one or more patents.
For more information visit www.gentexcorp.com/patents

1004004 REV.C


Copyright © 2025 Gentex Corporation. Ops-Core is a registered trademark of Gentex Corporation or its affiliates.
AMP is a trademark of Gentex Corporation or its affiliates.

INSTALLATION

CONNECTING AMP HEADSET DOWNLEAD

Connect the low profile end of the download cable to either the left or the right side of the headset (user's preference). The download cable will have a triangular (▲) marking on the Fischer connector.

Fischer
Connector
End




DISCONNECTING AMP HEADSET DOWNLEAD

Disconnect the download cable from the headset by pulling down on the outer sleeve of the connector to unlock it.

NOTE: DO NOT attempt to disconnect the download cable by pulling the cable itself.

Outer Sleeve



CABLING OPTIONS



Left Download
Connector

Right Download
Connector



Connecting to the Intercom System (ICS)

(Left or Right Earcup)

1. Connect the download cable to either the Left or Right Earcup Connector (Ensure proper key alignment).
2. Connect the download to the U94 input of the ICS system or PTT.

