



# Riot / Breaching Visor



The Ops-Core Riot/Breaching Visor offers modular, rapidly-employed face protection for operators with Ops-Core ARC Rail-equipped helmets. The 3mm thick visor smoothly pivots up and down to provide full face protection as needed. The Riot Visor also comes in a short trim variation to be compatible with various gas masks.

## KEY FEATURES

### Seamless Integration with Ballistic Helmets

Ops-Core FAST® and Sentry™ helmets, and Gentex ACH/TBH helmets can seamlessly incorporate the Riot Visor, further increasing the scalability by upgrading the protective posture through the addition of the face shield to the helmet.


### Stable, Secure Attachment

The Riot/Breaching Visor attaches to rails without tools and creates a seal to the front of the helmet shell. Center of gravity is less of a concern with the Riot/Breaching Visor because the overall system weight is a lot less.

1. Riot/Breaching Visor assembly fits most sizes of Ops-Core FAST and Sentry helmets, and Gentex ACH/TBH style helmets (*Not compatible with XL and XXL RF1 Helmets, and fitting on XL and XXL Fast helmets is significantly more difficult*)
2. Ballistic protective lens with hard-coated outside and anti-fog inside (available in full and short trim versions)
3. Fore/Aft adjustment maintains effective seal with different helmet geometries as well as increases offset to accommodate masks and other equipment as needed
4. Rail interface locking system provides solid platform for the Riot/Breaching Visor
5. Friction pivot secures Riot/Breaching Visor at any angle
6. Folding arms for smaller storage footprint
7. Pivots up and down and will remain in set position
8. Riot/Breaching Visor gasket minimizes the chance that liquids will drip behind the lens
9. Pinlock Anti-Fog Inert (*below, sold separately*) is specifically designed to absorb moisture and prevent fogging while keeping the field of vision clear and the focus on the mission

Product Category	Riot/Breaching Visor
Protection Level	Conforms to EN 166:2001 visor requirements. Tested and passed STANAG 2920 Ed3 criteria, 17gr frag v50 of 705ft/s.
Construction/Materials	High impact optical grade polycarbonate
Protection Area	62 in <sup>2</sup> (400 cm <sup>2</sup> )
Viewport Width	15" (38 cm)
Viewport Height	7.5" (19 cm)
Viewport Thickness	0.12" (3 mm)
Weight	1.2 lbs (544.3 g)

Note: All measurements are +/- 3% tolerance



## Contact Us

Ops-Core is committed to designing advanced performance capabilities for the elite warrior. For more information regarding the Ops-Core Riot/Breaching Visor, contact Ops-Core Customer Service at +1 888.894.1755 or [groundcs@gentexcorp.com](mailto:groundcs@gentexcorp.com). The Ops-Core Riot/Breaching Visor is controlled for export by the U.S. Export Administration Regulations (EAR) 15 CFR 730-774. The export of this helmet and related technical information requires prior authorization from the U.S. Government.