



# ALUMINIZED FABRICS

Protection You Can Count On. Value You Can't Beat.

## Comprehensive Fabric Line

Field proven for over fifty years, Dual Mirror® is the most durable brand of aluminized fabric in the industry. Each roll is thoroughly tested and provides uncompromising function, appearance, and superior performance even in the most demanding applications. With over twenty aluminized fabrics to choose from and an expert team to guide you in your selection, you can be assured you'll get the right fabric for your specific needs.

Classification	Style Number	Fabric Description	Weights	Certification
<b>Preox®</b>	Flexir® 1079	Knit Fleece with Dual Mirror	408 gm / m <sup>2</sup> ■ 12.0 oz / yd <sup>2</sup>	EN ISO 11612:2010 HR (Pass A1, A2, B1, C4, D3, E3, F1) Tensile: Pass   Tear: Pass
	Flexir® 1079B	Black Knit Fleece with Dual Mirror	440 gm / m <sup>2</sup> ■ 13.0 oz / yd <sup>2</sup>	EN ISO 11612:2010 HR (Pass A1, A2, B1, C4, D3, E3, F1) Tensile: Pass   Tear: Pass
	1083	Korspun I® with Dual Mirror	440 gm / m <sup>2</sup> ■ 13.0 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4, D3, E3) ■ EN ISO 11612:2010 1086 HR (Pass A1, A2, B1, C4, D3, E3, F1) Tensile: Pass   Tear: Pass
	1086	Korspun I with Dual Mirror	645 gm / m <sup>2</sup> ■ 19.0 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4, D3, E3) ■ EN ISO 11612:2010 1086 HR (Pass A1, A2, B1, C4, D3, E3, F1) Tensile: Pass   Tear: Pass
	1100-3	Herringbone with Dual Mirror & Neoprene Coating	610 gm / m <sup>2</sup> ■ 18.0 oz / yd <sup>2</sup>	EN 407
	1100-4	Herringbone with Dual Mirror	575 gm / m <sup>2</sup> ■ 17.0 oz / yd <sup>2</sup>	EN ISO 11612:2010 HR (Pass A1, A2, B1, C4, D3, E3, F1) Tensile: Pass   Tear: Pass
	1150-1	Herringbone with Neoprene Coating	540 gm / m <sup>2</sup> ■ 16.0 oz / yd <sup>2</sup>	
	1150-2	Herringbone with Neoprene Coating	595 gm / m <sup>2</sup> ■ 17.5 oz / yd <sup>2</sup>	
<b>PFR Rayon</b>	1006	Herringbone with Dual Mirror	510 gm / m <sup>2</sup> ■ 15.0 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4, D3, E3)
	1017	Herringbone with Dual Mirror	645 gm / m <sup>2</sup> ■ 19.0 oz / yd <sup>2</sup>	
	1019	Basketweave with Dual Mirror	645 gm / m <sup>2</sup> ■ 19.0 oz / yd <sup>2</sup>	
<b>Korspun I®</b>	1081	Aramid/Fiberglass Plain Weave with Dual Mirror	645 gm / m <sup>2</sup> ■ 19.0 oz / yd <sup>2</sup>	EN 531 (Pass A, B2, C4, D2, E3)
	1081-1	Aramid/Fiberglass Plain Weave with Dual Mirror	645 gm / m <sup>2</sup> ■ 19.0 oz / yd <sup>2</sup>	

Classification	Style Number	Fabric Description	Weights	Certification
<b>Aramids</b>	1054	Felt with Dual Mirror®	425 gm / m <sup>2</sup> ■ 12.5 oz / yd <sup>2</sup>	NFPA 1971-2018  NFPA 1971-2018 ■ EN ISO 11612: 2010 HR (Pass A1, A2, B1, C4, D2, E3, F1) Tensile: Pass   Tear: Pass  NFPA 1971-2018 EN 531 (Pass A, B1, C4)
	1056	Meta Aramid Twill with Dual Mirror	290 gm / m <sup>2</sup> ■ 8.5 oz / yd <sup>2</sup>	
	Flexir® 1088	Para Aramid Ripstop Knit with Dual Mirror	290 gm / m <sup>2</sup> ■ 8.5 oz / yd <sup>2</sup>	
	1091	Para Aramid Twill with Dual Mirror	375 gm / m <sup>2</sup> ■ 11.0 oz / yd <sup>2</sup>	
	1095	Para Aramid Twill with Dual Mirror	240 gm / m <sup>2</sup> ■ 7.0 oz / yd <sup>2</sup>	
	1320	1500 Denier Para Aramid	475 gm / m <sup>2</sup> ■ 14.0 oz / yd <sup>2</sup>	
	1350	Para Aramid Twill	270 gm / m <sup>2</sup> ■ 8.0 oz / yd <sup>2</sup>	
<b>Fiberglass</b>	1014	DE Fiberglass Satin with Dual Mirror	545 gm / m <sup>2</sup> ■ 16.0 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4, D1, E2)
	1016	Textured Fiberglass Plain Weave with Dual Mirror	745 gm / m <sup>2</sup> ■ 22.0 oz / yd <sup>2</sup>	
	1018	BC Fiberglass Satin with Dual Mirror	545 gm / m <sup>2</sup> ■ 16.0 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4, D1, E2)
	1022	Textured Fiberglass Plain Weave with Dual Mirror	950 gm / m <sup>2</sup> ■ 28.0 oz / yd <sup>2</sup>	
	1025	Fiberglass Satin with Dual Mirror	375 gm / m <sup>2</sup> ■ 11.0 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4, D1, E1) ■ EN ISO 11612:2008 (Pass A1, A2, B1, C4, D1, E1) (Pass 6.2, 6.5.1, 6.5.2)
	1299-074	Fiberglass Satin with Dual Mirror	180 gm / m <sup>2</sup> ■ 5.3 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4)
<b>PBI® Para Aramid</b>	Flexir® 1097	PFR Rayon Fleece with Dual Mirror	320 gm / m <sup>2</sup> ■ 9.5 oz / yd <sup>2</sup>	EN 531 (Pass A, B1, C4, D2, E1)
	Flexir® 1098	Ripstop Knit with Dual Mirror	240 gm / m <sup>2</sup> ■ 7.0 oz / yd <sup>2</sup>	NFPA 1971-2018
<b>Polyester</b>	1061	Polyester Plain Weave with Dual Mirror	270 gm / m <sup>2</sup> ■ 8.0 oz / yd <sup>2</sup>	

#### Contact Us

**Lou Ott** - Textile Sales Manager

Tel: 570.282.8514 ■ Fax: 570.282.8555 ■ lott@gentexcorp.com

**Megan Rude** - Inside Sales Representative

Tel: 570.282.8549 ■ Fax: 570.282.8555 ■ mrude@gentexcorp.com

Gentex Corporation is committed to designing innovative industrial safety solutions that protect people from immediate and long-term health and safety hazards present in their work environments, while enhancing workplace performance. For more information on Dual Mirror Aluminized Fabrics and our full line of industrial safety solutions, visit [www.gentexcorp.com/aluminizedfabric](http://www.gentexcorp.com/aluminizedfabric). Like us at [facebook.com/Gentexcorp](https://facebook.com/Gentexcorp) or follow us on Twitter @Gentex\_Corp.