



# FAST<sup>®</sup> BUMP

## High Cut Helmet System

- The FAST Bump high cut shell is designed for less extreme environments where exposure to great blunt trauma forces is limited or non-existent, or where the primary need is for integration of mission configured components.
- Molded front NVG mount. 4 position Accessory Rail Connectors (ARCs), and external side VELCRO<sup>®</sup> brand loop.
- Vent holes for increased ventilation and water drainage.
- Non-ballistic high-cut shell provides a low cost alternative to the FAST Carbon.
- Available with two suspension/retention options.

### SPECIFICATIONS

**Performance Specification:** BS EN 1385: 2012, Ops-Core FAST Bump Performance Specification PS-1145

**Shell Construction:** Injection Molding







**Areal Density:** N/A

**Shell Thickness:** 0.098" (2.50 mm)

**Shell Geometry (Curvature):** FAST Curvature

**Cut Style (Side Protection):** High Cut

**Available Colors:**

 Urban Tan	 Foliage Green	 Black
 MultiCam <sup>®</sup>	 Desert MARPAT	 Red

**Available Sizes:** Medium (S/M\*), Large (M/L\*), X-Large (L/XL\*)

\*FAST Bump helmets are molded with a visible split sizing. When ordering replacement parts for this helmet, use the single size indication.

Available Sizes	Medium	Large	X-Large	XX-Large
<b>Head Size (Circumference)</b>	20 7/8 - 22 in (53-56 cm)	22 - 23 1/4 in (56-59 cm)	23 1/4 - 24 3/8 in (59-62 cm)	N/A
<b>Square Coverage</b>	153.14 in <sup>2</sup> (988 cm <sup>2</sup> )	164.77 in <sup>2</sup> (1063 cm <sup>2</sup> )	179.34 in <sup>2</sup> (1157 cm <sup>2</sup> )	N/A
<b>Shell Weight</b>	0.67 lbs (305 g)	0.68 lbs (310 g)	0.71 lbs (324 g)	N/A

Note: All measurements are +/- 3% tolerance

### Contact Us

Ops-Core is committed to designing advanced performance capabilities for the elite warrior. For more information regarding the Ops-Core FAST Bump High Cut Helmet System, contact Ops-Core at 617.670.3547 or sales@ops-core.com. The FAST Bump is subject to the U.S. Export Administration Regulations (EAR) 15 CFR 730-774. The export of this item and related technical information may require prior authorization from the U.S. Government.

**Gentex Corporation** 324 Main Street Simpson, PA 18407 Tel: 617.670.3547 Fax: 570.282.8555 sales@ops-core.com

[www.ops-core.com](http://www.ops-core.com)