



FAST[®] SF

Next Generation Headborne System

The New FAST SF is Ops-Core's lightest weight ballistic helmet system yet. This weight reduction is enabled by the introduction of three new subsystems: the next-generation FAST SF ballistic shell, the LockDown[™] Liner, and the Head-Loc[®] Flex chinstrap.

- Ballistic protection from 9mm rounds (1200 f/s) with a shell weight of just 1.23 lbs/557 g (Size L) the FAST SF offers the same level of ballistic protection as its predecessor but with a 10% reduction in overall system weight.
- LockDown Liner System incorporates a user-customizable suspension system with multiple strategically placed pads, encouraging airflow. The LockDown Comfort Liner, featuring moisture-wicking fabric and reticulated foam, offers adaptable density for diverse head shapes and comfortably supports heavy VAS and NVG systems.
- LockDown conformable nape pad and cable Occ-Dial[®] offer enhanced stability, securing a larger contact area on the rear of the user's head, adapting to individual contours for an improved fit compared to other, more rigid systems.
- LockDown cable system enables an interference-free fit with headband communication systems.
- Redesigned Head-Loc Flex retention system introduces a unique convertible chin cup that can be worn either over or under the chin, eliminating the need for a mask extender with the O2 and CBRN kit for most users.
- PowerPath[™] ARC Rail system provides a lightweight mounting solution for Ops-Core headborne systems and features a unique, behind the rail channel for the safe routing of NVG cables.
- Lightweight Modular Bungee Shroud (MBS) reduces snag hazards and features carabiner clips to improve NVG retention and stability while reducing interference with other rail-mounted accessories.
- External VELCRO[®] Brand loop kit allows for quick and easy attachment and detachment of headborne accessories.



Featuring the all new LockDown Liner System



Head-Loc Flex convertible chin cup can be worn over or under the chin



SPECIFICATIONS

Performance Specification:** Modified and Abbreviated Family of Tactical Headborne Systems, dated June 30th 2017; Ops-Core Performance Specification FAST SF PS-1508

NIJ Standards: NIJ 0106.01 with NIJ 0108.01 Level IIIA (9mm FMJ @ 1,400 ft/s) Threat

Compression Testing: Top-Bottom = .020" (0.51 mm) Max @ 400 lbs. (181.44 kg), Side-Side = .125" (3.18 mm) Max @ 300 lbs. (136.08 kg) lbs.

Environmental Resistance: Temperature storage and operating at ambient, cold -60° F (-51° C), and hot +160° F (71° C), temperature shock, flame resistance, altitude, seawater, field agent resistance, weatherometer

Blunt Impact Protection: 150 g's maximum at 10 ft/s. Maximum allowable dent 0.023"

Ballistic Testing:

**Not all suspension/retention options are tested to full stated standards.

| Projectile | Minimum V50 BL(P) at 0°(±5°) Obliquity (ft/s) | Minimum V50 BL(P) at 0°(±5°) Obliquity (m/s) |
|------------------------|---|--|
| 2 - Grain RCC | 4,200 | 1,280 |
| 4 - Grain RCC | 3,475 | 1,059 |
| 16 - Grain RCC | 2,475 | 754 |
| 64 - Grain RCC | 1,750 | 533 |
| 17 - Grain FSP | 2,297 | 700 |
| 124 - Grain 9mm FMJ*** | 1,195 (+50/-0) | 364 (+15/-0) |

***9mm is V0 tested at this velocity with Backface Transient Deformation (BTD) under 23.4mm (Crown), 27.1mm (Sides), 29mm (Front), and 19.1mm (Rear) when tested on multi-sized clay-filled headforms in accordance with the USSOCOM FTHS Specification.



FAST SF

SPECIFICATIONS (CONTINUED)

| | |
|-------------------------------------|--------------------|
| Shell Construction: | Two-stage non-slit |
| Shell Thickness: | 0.170" (4.32mm) |
| Shell Geometry (Curvature): | FAST |
| Cut Style (Side Protection): | High Cut |

Available Sizes: Medium (M), Large (L), X-Large (XL), XX-Large (XXL)

Available Colors:



SHELL SIZING & COVERAGE

| Available Sizes | Medium | Large | X-Large | XX-Large |
|----------------------------------|--|--|---|---|
| Head Size (Circumference) | 20 7/8 - 22 in (53-56 cm) | 22-23 1/4 in (56-59 cm) | 23 1/4 - 24 3/8 in (59-62 cm) | 24 3/8 - 25 1/8 in (62-64 cm) |
| Square Coverage | 137 in ² (884 cm ²) | 148 in ² (955 cm ²) | 163 in ² (1052 cm ²) | 171 in ² (1103 cm ²) |

SHELL WEIGHT**

| Available Sizes | Medium | Large | X-Large | XX-Large |
|---|-----------------|-----------------|-----------------|-----------------|
| FAST SF Shell Weight (Shell with paint & edge band) | 1.12 lbs (508g) | 1.23 lbs (557g) | 1.32 lbs (597g) | 1.34 lbs (610g) |

SYSTEM WEIGHT**

| Available Sizes | Medium | Large | X-Large | XX-Large |
|---|-----------------|-----------------|-----------------|------------------|
| FAST SF System Weight (FAST SF Shell with LockDown Liner System) | 1.99 lbs (904g) | 2.09 lbs (949g) | 2.19 lbs (992g) | 2.23 lbs (1014g) |

(**Estimated calculations of weights) Note: All measurements are +/- 3% tolerance

Contact Us

Ops-Core is committed to designing advanced performance capabilities for the elite warrior. For more information regarding the Ops-Core FAST SF High Cut Helmet System, contact Ops-Core Customer Service at +1 888.894.1755 or groundcs@gentecorp.com. The FAST SF High Cut Helmet System is controlled for export by the U.S. Export Administration Regulations (EAR) 15 CFR 730-774. The export of this helmet and related technical information requires prior authorization from the U.S. Government.